



## **Platinum Oil™ Mineral 10W-30 SM/CI-4**

**(Available in 3 litre packing)**

### **DESCRIPTION**

**Platinum Oil™ 10W-30 SM/CI-4** is a premium mineral engine oil. Manufactured to meet requirements of almost all modern multi valves with or without turbo chargers. It provides smoother, cooler and quieter engines. Its advanced additive system ensures excellent control over soot induced wear, high temperature deposits, corrosion, foaming and oxidation stability. This engine oil is manufactured with high safety measures and quality control according to ISO 9001:2000 standard.

Highly recommended for all types of engines such as fuel injection, turbo-charge, multi-valves and carburetor.

### **ADVANTAGES**

- ~ Protects engine internal corrosion.
- ~ Reduces carbon, acid and sludge formation.
- ~ Keeps engine running clean and efficient.
- ~ Provides optimum engine performance.
- ~ Ensures optimum engine protection against wear.
- ~ Ensures smoother, cooler and quieter engines.

### **PERFORMANCE STANDARD COMPLIANCE**

- ~ SAE 10W-30 Viscosity Grade
- ~ Mercedes-Benz 229.1, 228.1
- ~ API SM/CI-4
- ~ VW 500/501/505
- ~ MIL-L-2104D
- ~ ACEA A2-96#2, A3-98, B2-98, B3-98, E2-96#2

**TYPICAL CHARACTERISTICS**

<i>Characteristics Method</i>	<i>Unit</i>	<i>Method</i>	<i>Typical Value</i>	<i>Specification</i>	
				Min	Max
<b>Kinematic Viscosity @ 100°C</b>	cSt	ASTM D445	15.00	13.8	16.3
<b>Kinematic Viscosity @ 40°C</b>	cSt	ASTM D445	< 158.3	-	158.3
<b>Density @ 27°C</b>	kg/m <sup>3</sup>	ASTM D1298	0.872	0.86	0.88
<b>Flash Point</b>	°C	ASTM D93	220	208	-