



**Platinum Oil™ Semi Synthetic 10W-30 SM/CI-4 With ZFT Formula**  
(Available in 4 litre packing)

**DESCRIPTION**

**Platinum Oil™ 10W-30 SM/CI-4** is a premium semi-synthetic engine oil with ZFT formula (Zero Friction Technology). It is recommended for either newer vehicles, high performance engines, or vehicles that usually travel either in the town or locally. It is especially suitable for smaller engines and high speed performance engines. It also consists of additives such as a high grade anti-wear, viscosity improver, detergent, dispersant, anti-foaming, corrosion inhibitor & Anti-oxidant. It is specially formulated for use in gasoline (petrol) and diesel engines. It is manufactured with high safety measure and quality control according to ISO 9001:2008 standard. Shelf life provided is 3 to 3 ½ years.

**ADVANTAGES**

- ~ Reduces wear by providing protection at a shortest time especially during cold starts
- ~ Recommends for Myvi, Alza, Kancil, Rusa, Viva, Kembara, Nautica, Kenari, Kelisa, Kia, Hyundai, Jaguar, Honda, Toyota, Nissan, Mazda, Ford, Mercedes, BMW, Audi, Voxwagen, etc
- ~ Highly recommended for both smaller engines and high performance bigger engines capacity. It is advisable to follow auto manufacturer's recommendations
- ~ Recommends for new engine or engine in good operating conditions
- ~ Ensures maximum engine performance and power
- ~ Reduces oxidation in all circumstances and at all situation
- ~ Reduces carbon, acid and sludge formations
- ~ Ensures smoother, cooler and quieter engines. Protection against internal corrosion
- ~ Keeps engine running clean and efficient

**PERFORMANCE STANDARD COMPLIANCE**

- ~ SAE 10W-30 Viscosity Grade
- ~ API SM/CI-4

**TYPICAL CHARACTERISTICS**

<i>Characteristics Method</i>	<i>Unit</i>	<i>Method</i>	<i>Typical Value</i>
<b>Kinematic Viscosity @ 100°C</b>	cSt	ASTM D445	11.3
<b>Kinematic Viscosity @ 40°C</b>	cSt	ASTM D445	103.9
<b>Density @ 27°C</b>	kg/m <sup>3</sup>	ASTM D1298	0.8735
<b>Flash Point</b>	°C	ASTM D93	208