



Platinum Oil™ Synthetic Gold 10W-40 SM/CI-4 with ZFT Formula
(Available in 4 litre packing)

DESCRIPTION

Platinum Oil™ Synthetic Gold 10W-40 SM/CI-4 is formulated using high quality synthetic oil component in combination with superior quality mineral base oil. Platinum Oil Synthetic Gold 10W-40 SM/CI-4 engine oil manufactured to meet requirements of all modern multi valves with or without turbo charges. It provides fuel economy and increases the oil change intervals under normal & extreme operating conditions. It is protect cylinder walls, pistons, bearing and valve train component beyond the levels of conventional passenger car motor oils.

Highly recommended for all types of engines such as fuel injection, turbo-charge, multi-valves and carburetor.

ADVANTAGES

- ~ Improves engine performance and power.
- ~ Ensures longer engine life.
- ~ Reduces fuel consumption as the oil is lighter.
- ~ Protects against engine internal corrosion and rust.
- ~ Keeps engine running clean and efficient.
- ~ Formulated for protection during cold start.
- ~ Ensures optimum engine protection against wear.
- ~ Ensures smoother, cooler and quieter engines.

PERFORMANCE STANDARD COMPLIANCE

- ~ SAE 10W-40 Viscosity Grade
- ~ Mercedes-Benz 229.1, 228.1
- ~ API SM/CI-4
- ~ VW 500/501/505
- ~ MIL-L-2104D
- ~ ACEA A2-96#2, A3-98, B2-98, B3-98, E2-96#2

TYPICAL CHARACTERISTICS

<i>Characteristics Method</i>	<i>Unit</i>	<i>Method</i>	<i>Typical Value</i>
Kinematic Viscosity @ 100°C	cSt	ASTM D445	15.87
Kinematic Viscosity @ 40°C	cSt	ASTM D445	116.4
Density @ 15°C	g/ml	ASTM D4045	0.8846
Viscosity index	-	ASTM D2270	145
Flash Point	°C	ASTM D92	230.0