



Platinum Oil™ Semi Synthetic 15W-50 4T With ZFT Formula
(Available in 1 litre packing)

DESCRIPTION

Platinum Oil™ 15W-50 with ZFT (Zero Friction Technology) is a premium engine oil. It is a SAE 15W-50 grade which consist of high-grade additives, viscosity improver, corrosion inhibitor & Anti-oxidant. It is specially formulated for use in motorcycle gasoline (petrol) engine i.e 4-stroke & 2-stroke engines. It is provides high temperature protection at all time, exceeding the toughest standard thermal breakdown.

ADVANTAGES

- ~ Ensures optimum engine protection against wear.
- ~ Anti wear at least 5 times better than normal engine oil.
- ~ Ensure longer engine life.
- ~ Oil change duration one time longer than normal oil.
- ~ Ensures maximum engine performance and power.
- ~ Ensures good pick-up power.
- ~ Ensures smoother, cooler and quieter engines.
- ~ Keeps engine running clean and efficient.

PERFORMANCE STANDARD COMPLIANCE

- ~ SAE 15W-50 Viscosity Grade
- ~ API SM

TYPICAL CHARACTERISTICS

<i>Characteristics Method</i>	<i>Unit</i>	<i>Method</i>	<i>Typical Value</i>
Kinematic Viscosity @ 100°C	cSt	ASTM D445	19.4
Kinematic Viscosity @ 40°C	cSt	ASTM D445	145.7
Density @ 27°C	kg/m ³	ASTM D1298	0.8906
Flash Point	°C	ASTM D93	> 210
Colour	-	Visual	Yellow