



**Platinum Oil™ Automatic Transmission Fluid – Dexron III**  
(Available in 4 litre packing)

**DESCRIPTION**

Platinum Oil™ ATF DEXRON III consist of high quality paraffinic base oil and additive systems to provide excellent foam resistance, corrosion and wear protection. It is reinforced with specially selected friction modifiers to meet the demanding frictional requirements of the automatic transmission. Shelf life provided is 3 to 3 ½ years.

**ADVANTAGES**

- ~ Ensures long servicing life
- ~ Provides high form stability
- ~ Superb anti-wear properties
- ~ Smoother & quieter automatic transmission
- ~ Excellent frictional, oxidative and thermal stability
- ~ Provides anti rust protection and lower sludge formation
- ~ Provides good start operation in cold climates by low temperature fluidity

**PERFORMANCE STANDARD COMPLIANCE**

- ~ GM Dexron III, Dexron III E
- ~ Mercon fluids
- ~ Allison C-4 Fluid
- ~ Caterpillar TO-2 Lubricant
- ~ MIL-L-2104 D

**TYPICAL CHARACTERISTICS**

<i>Characteristics Method</i>	<i>Unit</i>	<i>Method</i>	<i>Typical Value</i>
<b>Kinematic Viscosity @ 100°C</b>	cSt	ASTM D445	7.5
<b>Kinematic Viscosity @ 40°C</b>	cSt	ASTM D445	37.0
<b>Density @ 27°C</b>	kg/m <sup>3</sup>	ASTM D1298	0.867
<b>Pour Point</b>	°C	-	-25
<b>Flash Point</b>	°C	ASTM D93	202
<b>Appearance</b>	-	-	RED